

# Statistical radar imaging of diffuse and specular targets using an expectation-maximization algorithm

Aaron D. Lanterman  
([lanterma@ifp.wustl.edu](mailto:lanterma@ifp.wustl.edu))

Coordinated Science Laboratory  
Univ. of Illinois  
1308 W. Main  
Urbana, IL 61801

This work was supported by DARPA Contract  
F49620-98-1-0498, administered by AFOSR.  
<http://www.ifp.uiuc.edu/~lanterma/darpa>

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>21 APR 2000</b>		2. REPORT TYPE		3. DATES COVERED <b>00-00-2000 to 00-00-2000</b>	
4. TITLE AND SUBTITLE <b>Statistical radar imaging of diffuse and specular targets using an expectation-maximization algorithm</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>University of Illinois at Urbana-Champaign, Coordinated Science Laboratory, Urbana, IL, 61801</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES <b>presented at SPIE Aerosense 2000, Orlando, FL, April 2000. U.S. Government or Federal Rights License</b>					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>16</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

# Models for Received Radar Data

- Received data  $\mathbf{r} = \mathbf{\Gamma}^H \mathbf{c} + \mathbf{w}$ , where
  - $\mathbf{c}$  = complex target reflectance
  - $\mathbf{\Gamma}$  = linear observation mechanism
  - $\mathbf{w} \sim CN(0, N_0 I)$
- Examples of  $\mathbf{\Gamma}$ :
  - Simple range profiling: Samples of transmitted waveform (representing convolution)
  - Delay-doppler imaging: Transmitted waveform multiplied by sinusoids
  - Tomographic imaging: Transmitted waveform with partial Radon transform
- In target detection,  $\mathbf{c}$  is often treated as random vector. In target imaging,  $\mathbf{c}$  is more often treated as an unknown deterministic parameter. Here we explore random models for  $\mathbf{c}$  for imaging purposes.

# Models for Target Reflectance

From Shapiro:

- Diffuse/speckle:  $\mathbf{c}_d \sim CN(0, \mathbf{\Sigma})$ 
  - $\mathbf{\Sigma}$  is a diagonal covariance
  - $\mathbf{s} = \text{diag}(\mathbf{\Sigma})$  called the *scattering function*
  - Goal: estimate  $\mathbf{s}$
- Specular/glint:  $\mathbf{c}_s = \mathbf{b} \times \exp[j\theta]$ 
  - $\theta \sim$  i.i.d. uniform over  $[0, 2\pi)$
  - $\mathbf{b}$  is a deterministic *glint reflection coefficient*
  - $\times$  is elementwise multiplication
  - Goal: estimate  $\mathbf{b}$
- Mixed model:  $\mathbf{c} = \mathbf{c}_d + \mathbf{c}_s$ 
  - Goal: estimate  $\mathbf{s}$  and  $\mathbf{b}$
  - Tends to be overparameterized

# EM Algorithm for Diffuse Imaging

- For diffuse imaging,  $\mathbf{r} \sim \mathcal{CN}(0, \mathbf{\Gamma}^H \mathbf{\Sigma} \mathbf{\Gamma} + N_0 \mathbf{I})$ , yielding a structured covariance estimation problem
- No obvious closed-form formula for ML estimate
- Iterative EM algorithm by Snyder-O'Sullivan-Miller:

$$\sigma_i^{new} = \sigma_i^{old} - (\sigma_i^{old})^2 [\mathbf{\Gamma} \mathbf{K}^{-1} \mathbf{\Gamma}^H - \mathbf{\Gamma} \mathbf{K}^{-1} \mathbf{r} \mathbf{r}^H \mathbf{K}^{-1} \mathbf{\Gamma}^H]_{ii},$$

where

$$\mathbf{K} = \mathbf{\Gamma}^H \mathbf{\Sigma}^{old} \mathbf{\Gamma} + N_0 \mathbf{I}$$


- Enjoys usual properties of EM algorithms
  - Likelihood increases at each iteration
  - Iterates guaranteed to be nonnegative

## What About Specular Imaging?


- Specular  $\mathbf{r}$  is vastly more complicated
  - Not aware of a closed form for the density on  $\mathbf{r}$
- If the columns of  $\mathbf{\Gamma}$  have a sufficient non-zero entries:
  - $\mathbf{r}$  consists of sums of indep. 0-mean random variables
  - By CLT, *marginals* on  $\mathbf{r}$  approx. 0-mean Gaussian
  - $\mathbf{r}$  “almost Gaussian” in the spirit of Mallows
- Motivates trying the diffuse EM algorithm on the specular case

# Phantoms for Simulations

- Three point scatterers:




- Rotating sphere:




# Transmitted Waveform

- Specular realization:




- Autocorrelation:






# Data from Three Point Scatterer

- Data from three point scatterer:




# Results for Three Point Scatterer

- Matched filter output:




- At 1, 5, 10 and 20 EM iterations:




# Data for the Sphere


- Two diffuse realizations:



- Two specular realizations:



# Results for Diffuse Sphere



# Results for Specular Sphere



# Regularization Techniques

- Grenander's Method of Sieves
  - B-spline basis for  $f$  (Moulin 92)
  - Wavelet basis for  $\log(f)$  (Moulin 93)

- Penalized likelihood methods
  - Subtract penalty from likelihood

$$P(r|f) = L(r|f) - \alpha\Phi(f)$$

- Good's roughness penalty:

$$\Phi_G(f) = \int \left[ \frac{d}{dx} \sqrt{f(x)} \right]^2 dx$$

- Good's is equivalent to O'Sullivan's I-divergence penalty
  - Silverman's roughness penalty:

$$\Phi_S(f) = \int \left[ \frac{d}{dx} \log f(x) \right]^2 dx$$

- Simple modification of EM algorithm produces penalized likelihood estimates; amounts to nonlinearly smoothing the result of the maximization step at each iteration
  - Admits a Bayesian interpretation

# Expectation-Maximization-Smoothing Algorithms

- Suggested by Silverman for emission tomography
- Try different kinds of *ad hoc* smoothing steps
- A particular choice of smoothing may not correspond to any particular penalized likelihood method
- Good performance shown in emission tomography
- However, it's hard to prove whether such algorithms converge, and even harder to show what they converge to

## Directions for Future Work

- Implementation and comparison of various regularization techniques
- Current execution time of MATLAB implementation on Sun Enterprise 3500:

Image size	Total time	Time for inverse
20 x 20	15 seconds	6 seconds
32 x 32	8 minutes	4 minutes
40 x 40	32 minutes	13 minutes

- Improve computation time
  - Must find fast way of doing matrix inverse (or avoiding an explicit inverse altogether)
  - Speed up multiplies by  $\mathbf{\Gamma}$
  - Fast EM Variants (SAGE, etc.)
- Statistical formulation provides criteria for radar waveform design (via Cramer-Rao bounds, etc.)
- Other applications
  - Radar astronomy
  - Direction finding?



# Bibliography

- J. Shapiro, B.A. Capron, and R.C. Harney, “Imaging and target detection with a heterodyne-reception optical radar,” *Applied Optics*, 20(19):3292-3313, 1981.
- D.L. Snyder, J.A. O’Sullivan, and M.I. Miller, “The use of maximum-likelihood estimation for forming images of diffuse radar-targets from delay-doppler data,” *IEEE Trans. IT*, 35(3):536-548, 1989.
- C.L. Mallows, “Linear processes are nearly Gaussian”, *J. of Applied Prob.*, 4:313-329, 1968.
- P. Moulin, J.A. O’Sullivan, and D.L. Snyder, “A method of sieves for multiresolution spectrum estimation and radar imaging,” *IEEE Trans. IT*, 38(2):801-813, 1992.
- P. Moulin, “A wavelet regularization method for diffuse radar-target and speckle-noise reduction,” *J. of Mathematical Imaging and Vision*, 3(1):123-134, 1993.
- J.A. O’Sullivan, “Roughness penalties on finite domains,” *IEEE Trans. Image Proc.*, 4(9):1258-1268, 1995.
- B.W. Silverman, “On the estimation of a probability density function by the maximum penalized likelihood method,” *Annals of Stat.*, 10(3):795-810, 1982.
- B.W. Silverman, M.C. Jones, J.D. Wilson, and D.W. Nychka. “A smoothed EM approach to indirect estimation problems, with particular reference to stereology and emission tomography (with discussion),” *J. of the Royal Stat. Soc. B*, 52(2):271-324, 1990.